
# ₽CE Of CL₽CC

### **Technical Rider: May 2014**

Channel	Instrument	Mic / DI	Stand	Insert
No				
1	Drums L	XLR out *		Comp
2	Drums R	XLR out *		Comp
3	Kick	XLR out *		Comp
4	Snare	XLR out *		Comp
5	Samples L	XLR out *		Comp
6	Samples R	XLR out *		Comp
7	Bass Clean	DI		Comp
8	Bass FX	DI		
9	Bass Novation Synth	DI		Comp
10	Roland SPDS	DI		
11	Acoustic Gtr	XLR out		
12	Virus Synth L	DI		Comp
13	Virus Synth R	DI		Comp
14	Nord Synth L	DI		Comp
15	Nord Synth R	DI		Comp
16	Nick Vocal	SM58	Tall	Comp
17	Rory Vocal Dry (main)	SM58 XLR Out	Tall	Comp
18	Rory Vocal Wet FX Split	XLR Out	Tall	
19	Stan Vocal	SM58	Tall	Comp
20	Spare Vocal	SM58	Tall	Comp
21	Reverb Return	N/A	N/A	N/A

\*Output from an Audio Interface. All (#) lines are balanced XLR output.

#### Age of Glass - Stage Plan:



#### **Touring Party:**

**Rory:** Synths, Guitar, Lead Vocal **Nick**: Zen Drum, Samples, Backing Vocals **Stan:** Bass Guitar, Backing Vocals

**Jonny:** FOH Engineer - all tech enquires send to <u>Jonny@neuronproaudio.co.uk</u> or call 07894271605

#### PA Requirements:

Age of Glass are an electronic dance music act. The PA system must be of adequate power for the intended space with separate sub and mid high cabinets. It must have adequate headroom for live music. The music is very bass driven therefore subs must be of suitable size for the intended space.

#### **FOH Requirements:**

FOH console can be either analogue or digital.

Preferred digital consoles (in order of preference):

Soundcraft Vi or Si Midas Pro Yamaha M7 / LS9 (NO 01V / 03D!!!) Behringer X32

Preferred analogue consoles (in order of preference):

Midas Allen & Heath Soundcraft

#### NO MACKIE, ALTO, PHONIC, BEHRINGER OR YAMAHA please.

If an analogue console is to be used please ensure that adequate outboard units are provided. We ideally require 12 channels of compression although can be flexible if needed to be. Brands: DBX, Klark Teknik, Audient, LA Audio all fine. Please **NO BEHRINGER etc.** 

#### **Monitoring Requirements:**

We require a minimum of three separate monitor mixes on stage. ALL mixes MUST have 31 band graphic EQ inserted on the aux send. Ideally each mix should feature a pair of wedges but at a bare minimum mix two (centre vocal) must feature a pair. Wedges should ideally be passive and bi-amped with control for Mid and HF sections of the cabinet, preferably no active speakers. Each speaker should be a minimum of 450 watt RMS. Ideally wedges should be rung out before arrival in order to avoid any feedback issues.

## N.B. We are a very approachable bunch of souls, if you cannot meet the requirements stipulated on this rider then please <u>JUST LET US KNOW</u>.

100% preparation = 0% perspiration :-) Thanks in advance, A.O.G