IOTA PHI

The following technical requirements for the artist IOTA PHI are an integral part of their performance. If any or all of the specifications cannot be met, please **notify** the band and/or engineer **prior** to the show.

INPUT LIST

ch. 1	Vocals	Wireless Beta 58
ch.2	Laptop R	DI
ch.3	Laptop L	DI

OUTPUT LIST

Aux 1,2	Voc inear
Aux 3,4	Stereo Wedge

If in this case we don't have in ear monitors, we would like to ask for two monitors for the vocalist and one for the Live Electronics.

BACK LINE

1x Neumann km84 1x SHURE BETTA 58 4x DI 1x table for Laptop & Push Ableton Controller

MAIN P.A SYSTEM:

We need:

- a strong pressure in the very low frequencies SUBS on an auxiliary mix
- In-fill and delay speakers

Our preferences are (depending on the size of the room):

- 1 : D&B line array : J, V or Y series
- 2 : L-acoustics line array : K, Kara, V Dosc or DV Dosc
- 3: Meyer Sound line array: Leo, Lyon, Leopard or Mica 4:

Adamson line array: E-series or S-series

FOH

Soundcraft vi1, Midas Pro 2 etc.

MONITOR

Midas M32

Sound Engineer:

Nikos Goudinakis

(n.goudinakis@gmail.com +30 6947622156)

