Technical Rider

for

KIDS FLY

Updated 07.06.14

Subject to change

A professional-quality sound system should be installed, capable of producing a 120 dbs SPL signal in all frequencies in any space of the venue.

ACOUSTIC PRESSURE DURING THE CONCERT MUST BE SET BETWEEN 110 – 120 Db. IN CASE OF LEGAL LIMITATIONS, PLEASE CONTACT US AS SOON AS POSSIBLE.

The sound and lighting system must be assembled and functioning by the time the band arrives for sound check.

Sound check will be 1.5 hours not including stage assembly time. In case of festivals - A minimum 20 minute line check is required.

Mixer:


any digital mixer (preferred yamaha or digidesign)

Mixer Line Inputs

- 1. KICK Shure Beta52
- 2. SNR Shure Sm57
- 3. TOM Sennheiser E604
- 4. FLOOR Sennheiser E604
- 5. HH Shure Sm81
- 6,7. OH Shure Sm81 X2
- 8. BASS DI
- 9. GTR 1 Shure Sm57
- 10. GTR 2 Shure Sm57
- 11,12. COMP 1 (BASS) DI X2
- 13,14. COMP 2 (KEYS) DI X2
- 15,16. NORD (KEYS) DI X2
- 17. LEAD VOC Shure Sm58
- 18. B.VOC (DRUMS) Shure Beta 58
- 19. B.VOC (BASS) Shure Beta 58
- 20. B.VOC (KEYS) Shure Beta 58

Stage Plot:

KIDS-FLY STAGE PLOT



Monitor Section:

6 x 15" Bi AMP floor monitors

The monitors run on 6 different sends:

Send 1: 1x15" Drums **Send 2**: 1x15" Bass **Send 3**: 1x15" Gtr 1 **Send 4**: 1x15" Gtr 2

Send 5: 1x15" Keys

Send 6: 2x15" Lead Voc

For any inquires / questions / technical issues please feel free to call:

Noam Levinberg -

Ha Avodah 36, Tel Aviv, Israel Email: Noam@plutostudios.com

Phone: +972 545 696090 / 0545696090